

I-O PrintBox RPC



- Host Systems: ASCII (PC, LAN, UNIX, RISC/6000, VAX, Wang)
- Interface: Centronics parallel or RS-232 serial to IBM twinax or coax
- Power: 9V wall mount transformer
- Environment: Temperature: +40° to 110° F (+5 to 42° C)
Relative humidity: 20% to 85%
Optimum: 70° +/- 15° F (24° +/- 8° C)
- Size: 6 1/2" x 2 1/8" x 5 1/2" (16.5 x 5.4 x 14 cm)
- Approvals: FCC A; CISPER 22 class A

The I-O Print Box RPC **protects your investment** in IBM system printers when migrating to LAN, UNIX, or other ASCII environments.

The reverse protocol converter interfaces between the attached twinax or coax IBM (or compatible) system printer and a LAN, RISC/6000, or other ASCII-based host system.

The I-O Print Box RPC supports Epson FX or IBM Proprinter data streams at over 1,500 lines per minute (LPM). The integrated LCD front panel allows user-friendly customization, as well as status monitoring. The I-O Print Box RPC also offers a unique diagnostics port for quick problem resolution and configuration review using the additional ASCII printer port.

Introduce your system printer to the I-O Print Box RPC. Together, they can handle heavy-duty print jobs at a fraction of the cost of a new printer.

IBM Features:

Attaches to IBM 4234, 4214, 5256, 5224/25/56, 5219, and other SCS printers via twinax cable.

Attaches to IBM 4224, 4214, 3287/68 and other SCS printers via coax cable.

Supports IBM Proprinter and EPSON data streams

Multiple Applications

Supports Large ASCII Print Jobs

Plus a wide range of additional features that boost productivity and performance.

Features	Benefits
IBM Compatibility	Seamless connectivity to attached IBM (or compatible) system printers. The I-O Print Box RPC understands the limitations of your IBM printer and automatically ignores ASCII commands which are not supported by an IBM printer.
Integrated LCD Front Panel	Easy configuration and status monitoring through the integrated LCD front panel.
IBM Proprinter or Epson FX Data Streams	Supports the two most popular ASCII printer data streams for worry-free printing from the ASCII host
Fast Print Speeds	Supports print speeds of over 1,500 lines per minute (LPM) for full utilization of the attached system printer.
Parallel or Serial Connectors	Convenient attachment of ASCII hosts through standard parallel or serial cables.
Unique Diagnostics Port	Quick problem resolution, troubleshooting, and configuration review using the additional ASCII printer port.